



SAFETY DATA SHEET
AERISGUARD COIL DEFENSE

SECTION 1: IDENTIFICATION

- 1.1. Product Identifier
 - Product form : Liquid Mixture in aerosol can
 - Trade name : AERISGUARD COIL DEFENSE AEROSOL
 - Product code : AGUS-CT-A

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - 1.2.1 Relevant identified uses
For the treatment of air conditioning and refrigeration coils.

 - 1.2.2 Uses advised against
No additional information available

- 1.3 Details of the supplier of the Safety Data Sheet

Company Name: Aeris Environmental Ltd, Level 1, Unit 5 / 26-34 Dunning Ave, Rosebery, NSW 2018 AUSTRALIA
Phone: +61 2 8344 1315 Fax: +61 2 96970944

Aeris Environmental, LLC 28610 Hwy 290, Ste F09 #242, Cypress TX 77433

1.4

Emergency Contact number: Phone: AU +61 2 8344 1315
USA: 1-908 878 7985

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture
 - 2.1.1 According to GHS classification:
 - Physical hazard:
Flammable Aerosol category 1.
 - Health Hazard:
Eye irritation category 2
Skin irritation category 2
 - Environmental hazard:
Aquatic acute category 3

 - 2.1.2 According to NOHSC Flammable gas, eye irritation.



2.2 Label elements

Labelling according to GHS Hazard pictograms:



Signal word: DANGER Hazard statements:

H222 Extremely flammable aerosol
H229 Pressurised container: May burst if heated H319
Causes serious eye irritation
H315 Causes skin irritation

Precautionary statements (GHS):

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use. [As modified by IV ATP]
P264: Wash hands thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+352: IF ON SKIN: Wash with plenty of water/... [As modified by IV ATP]
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P332+313: If skin irritation occurs: Get medical advice/attention.
P337+313: If eye irritation persists get medical advice/attention.
P362: Take off contaminated clothing. [As modified by IV ATP]

Storage:

P410: Protect from sunlight.
P412: Do not expose to temperatures exceeding 50°C/122°F.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.



2.3 Other hazards

Inhaled: Irritating to respiratory tract and mucous membranes. Inhalation of alcohol vapour may result in headache, nausea and vomiting. High concentrations may cause central nervous system symptoms similar to “swallowed”.

Swallowed: Unlikely under normal occupational exposures. But swallowing ethanol may cause harmful central nervous system effects. Effects may include excitation, euphoria, headache, Dizziness, drowsiness, blurred vision, fatigue, Tremors, convulsions, loss of consciousness, Coma, respiratory arrest and death. Severe Acute intoxication may cause hypoglycaemia, Hypothermia, and extensor rigidity. Other effects may include decreased blood pressure Vomiting blood and blood changes. Aspiration into the lungs may cause pneumonitis.

Chronic: Chronic intoxication of alcohol by swallowing or repeated inhalation may cause degenerative changes in the liver, kidneys, hair, and gastrointestinal tract and heart muscle.

Special Toxic Effects due to alcohol:

Persons with pre-existing liver impairment, skin and respiratory disorders may be at an increased risk from Exposure. Ethanol may also cause adverse reproductive effects. Concurrent absorption of ethanol and some drugs may cause adverse health effects.

Ingestion of beverages containing ethanol by pregnant women is associated with “fetal alcohol syndrome” in their babies. The International Agency for Research of Cancer (IARC) has evaluated Alcohol drinking as “Group 1 – carcinogenic to humans”.

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS

Mixtures

NAME	Product identifier	%	Classification according to GHS
Benzalkonium chloride	CAS no. 68424-85-1	0.1 - 3	Acute tox 4 H302 Skin Corr. 1B H314 Eye Dam. 1 H318 Aquatic Acute 1 H400,
Ethanol	CAS no. 64-17-5	40 - 80	Flam. Liquid 2 H225: Highly flammable liquid and vapour. Eye Irrit. 2 H319: Causes serious eye irritation SCL >=



			50.0)
Butane	CAS no. 106-97-8	10 – 30	H220: Extremely flammable gas.H280: Contains gas under pressure; may explode if heated.
Propane	CAS no. 74-98-6	10 - 30	H220: Extremely flammable gas.H280: Contains gas under pressure; may explode if heated.
Ingredients determined not to be hazardous	NA	To 100%	-

SECTION 4: FIRST AID

4.1 Description of first aid measures

- Eye: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.
- Skin: Take off contaminated clothing. Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.
- Inhaled: Remove to fresh air, rest patient and seek Medical attention. Give artificial respiration if breathing stops.
- Swallowed: Give plenty of water to drink. Do NOT induce vomiting. Seek medical attention if symptom persists.

4.2 Most important symptoms and effects, both acute and delayed

Eye irritation and skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Advice to Doctor: Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Use water fog, dry chemical, carbon dioxide or foam. In the absence of water fog, a fine spray can be used.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Combustion will produce oxides of carbon and hydrocarbons.



5.3. Advice for firefighters

Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.

SECTION 6: SPILLAGE, ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective gloves and eye/face protection. For further information refer to Section 8 "Exposure controls/personal protection". Eliminate all sources of ignition. Ventilate area. Evacuate unnecessary personnel.

6.2. Methods and material for containment and cleaning up

Leaking cans should be placed in a plastic bag or an open pail until the pressure has dissipated. Spray water to the spilled liquid, contain with an inert absorbent and place in a container for disposal. Clean spill area thoroughly with water. Report large spills to authorities as required.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safe handling:

DO NOT SMOKE. EXTREMELY FLAMMABLE AEROSOL. Pressurised dispenser. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not spray on a naked flame or other ignition source. Do not pierce or burn even after use.

Hygiene measures:

Take care for general good hygiene and housekeeping. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat, hot surfaces, sparks, open flames and other ignition source.

7.3. Specific end use(s)

Use only as directed. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

8.1 Control parameters

These are guides only and do not represent 'no-effect' levels, which guarantee protection to every worker.



Worksafe Australia has established exposure standards for the following ingredients:

Standard Name	CAS No	TWA (ppm)	TWA (mg/m3)
Ethyl alcohol	64-17-5	1000	1880

8.2 Exposure controls

These measures are recommended on the basis of common application methods and may not be appropriate to all potential applications of the product. The user is responsible for carrying out a full risk assessment for their specific processes and systems of work.

Personal protective equipment:

Eye protection: Wear eye protection such as safety goggles. Hand

protection: Wear chemical resistant gloves.

Body protection: As necessary to prevent contact.

Respiratory protection: You must wear the prescribed solvent respirator. Use in a well ventilated area. Avoid breathing vapour or spray.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

The following are the properties of the liquid without the propellant: Appearance:

A clear, pink coloured alcoholic liquid

Boiling Point: 78 – 84 °C (172.4-183.2°F)

Specific gravity: 0.80 - 0.84 @ 20 °C (68°F)

Solubility in water: Forms a polymer film.

Reactivity in water/air: Not reactive

Incompatibility (materials to avoid) Strong oxidizers pH Level: 6.0-8.0

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Not reactive

10.2 Chemical stability

The mixture is stable at normal ambient temperature (5 – 25 °C or 41-77°F).

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Storing at temp above 25 °C(77°F).

10.1 Incompatible materials

Incompatible with oxidising agents and acids.

10.2 Hazardous decomposition products

Does not decompose when used as intended.



SECTION 11: TOXICOLOGICAL INFORMATION

Not available, the following is the toxicological information of the active ingredient in its pure form:

Benzalkonium chloride:

Acute:

Oral LD50(rat): 600 mg/kg

Dermal LD50(rabbit): 3000 mg/kg; >5mL/kg Inhalation

LC50 (rat, 1hr): 21.5 mg/L

Eye irritation (rabbit): Severe irritant/corrosive Skin

irritation (rabbit): Severe irritant/corrosive

Subacute:

Dermal toxicity (rabbit – 20 days – at dilution concentration, 800 ppm active solution): Exposure animals were topically applied at either 1, 2 or 4 mL/kg, daily for a period of 20 days. At exposure doses used, the only material related effects observed were mild transitory erythema.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity study of this preparation is not available, the following is the ecological toxicity of the active ingredients; Benzalkonium chloride (pure form): very toxic to aquatic life. Ingredients contained in this preparation comply with the biodegradability criteria of Regulation (EC) No 648/2004 on detergents. None of the ingredients are classified as bioaccumulative. This mixture does not contain any substances that are assessed as PBT or vPvB.

SECTION 13: DISPOSAL CONSIDERATIONS

Do not pierce or burn can even after use. Do not contaminate water, food or feed. Completely empty the can following the instruction for use on the label. Dispose of the package in a sanitary landfill, or by incineration, if allowed by State and local authorities. If burned, stay out of smoke.

SECTION 14: TRANSPORT INFORMATION

Class-2.1 Aerosol, Flammable. Transport according to local/international dangerous goods regulations.

UN No.:	1950
HazChem:	2(Y)E
Packing group:	II
Subsidiary risk	None

SECTION 15: REGULATORY INFORMATION

All the ingredients are listed in the AICS (Australian Inventory of Chemical Substances).



SECTION 16: OTHER INFORMATION

H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated. H302:

Harmful if swallowed

H314: Causes severe skin burns and eye damage H318:

Causes serious eye damage

H319: Causes serious eye irritation SCL:

Specific Concentration Limit H400: Very toxic
to aquatic life

The opinions expressed herein are those of qualified experts. We believe that the information contained herein is current as of the date of this SDS. Since the use of this information and these opinions and the conditions of use of the product are not within the control of Aeris Environmental Ltd it is the users' obligation to assure safe use of the product.

Date SDS revision: 23 Dec 2019

-END-